

Video Contact Center Call-o-Call®

Protocols Support

SS7 (ISUP, INAP, MAP, TCAP)
 CAMEL, IS.41 WIN, SMPP
 ISDN (worldwide)
 3GPP 3G-324M Rel 99 (TDM) / Rel 4 (NbUP), MONA
 ITU-T H.323, SIP RFC-3261
 T.38 and V.17 Fax

Supported codecs

H.263, H.264, MPEG4, AMR-NB, AMR-WB
 G.711 (PCM, ADPCM, uLaw, aLaw), G.723.1, G.726, G.729, GSM-FR

Video features

Transcoding with frame rate conversion, image rescale, I-Frame update
 Conference with custom video layout & SIP
 Overlay images & text
 Enhanced video bitrate controller
 Real-time Streaming
 DVR controls

Audio features

Audio Transcoding
 Conference with advanced gain control
 DTMF Processing (Tone Detection/Generation, RFC2833)
 Speech recognition (MRCP v1, v2, RTSP / RTP, SIP SDP)

Custom web & DB integration

HTTP / HTTPS	CORBA	MSSQL
SSH	TCP/IP	Oracle
XML	COM / DCOM	MySQL
FTP	SOAP	ODBC/OLE DB
RADIUS	RPC	

Administration and management

Graphical real-time monitoring & activity reporting tool
 Centralized Administration utility
 Audio/Video content management with import/export features

Service Creation Environment

IDE (Online/offline debugging, syntax highlight/code completion)
 Visual scenario and Q&A editor

Contact-center features

Cross-platform solution (Windows, Linux, Mac OS)
 CRM integration
 Improved call recording (Voice+Video)
 Powerful online & offline activity reporting

Integrated IVR scenarios


Voice-Video Portal
 Inbound/Outbound marketing campaigns
 Adult 18+
 Self-Banking
 Desktop co-browsing

Tech support levels

Languages: English, Russian.
 1st level: 24x7x365 phone/e-mail/web
 2nd level: work time (MSK time) phone/e-mail/web
 3rd level: e-mail only
 Fast hardware replacement

Specification

Power: 100-240 AC, -48 DC, up to 700W, Hot Plug and Redundant.
 Rack mount 19" 2U, 4U appliance
 Connectivity: E1, T1, Ethernet



©2010 Forte-IT. All Rights Reserved.



Forte-IT Ltd.

BP Rymantsevo, 4th Floor
 Moscow, Russian Federation,
 142784

tel: +7 495 783-0220
 e-mail: ct@forte-it.ru

www.forte-it.ru